

Conformal coating

ELPEGUARD® SL 1307 FLZ-HT

ELPEGUARD® SL 1307 FLZ-HT, colourless, is the same as our conformal coating **ELPEGUARD® SL 1307 FLZ-T**, colourless, but with a significantly higher viscosity and thixotropy. With this adjustment, the ink will not run off between the component leads. **ELPEGUARD® SL 1307 FLZ-HT** should only be applied by means of a dispenser.

Characteristics

Viscosity (ISO 3219 at 20°C)	4,000–7,000 mPas
Density (ISO 2811-1 at 20°C)	0.95–1.05 g/cm ³

Index FLZ = fluorescent, HT = highly thixotropic

For further information regarding the application, processing and properties of **ELPEGUARD® SL 1307 FLZ-HT**, please consult the technical report on our conformal coating **ELPEGUARD® SL 1307 FLZ-T** and [Application information sheet AI 1/1](#) "Processing instructions for **ELPEGUARD®** conformal coatings (thin film coatings)" for orientation purposes.

Disclaimer

All descriptions and images of our goods and products contained in our technical literature, catalogues, flyers, circular letters, advertisements, price lists, websites, data sheets and brochures, and in particular the information given in this literature are non-binding unless expressly stated otherwise in the Agreement. This shall also include the property rights of third parties if applicable.

The products are exclusively intended for the applications indicated in the corresponding technical data sheets. The advisory service does not exempt you from performing your own assessments, in particular as regards their suitability for the applications intended. The application, use and processing of our products and of the products manufactured by you based on the advice given by our Application Technology Department are beyond our control and thus entirely your responsibility. The sale of our products is effected in accordance with our current terms of sale and delivery.

ATTENTION! For new products, according to preliminary product information sheets, complete or adequate practical and test results are not always available which would permit a comprehensive assessment of such a product.

It is therefore imperative to exercise particular care in the testing of such products with regard to the application intended!

Any questions?

We would be pleased to offer you advice and assistance in solving your problems. Samples and technical literature are available upon request.